

Related Items



CO-002
TRIPOD



CO-007
TRIPOD



CO-005
SCOPE MOUNT



CO-011
ARCA RIFLE CLAMP



CO-013
BOWL RISER MOUNT



CO-004
RIFLE CLAMP



CO-K05
KIT



CO-K06
KIT



CO-04
KIT

Crux Ordnance
www.CruxOrd.com



Specifications and design are subject to change without notice.
© 2018

CruxOrd • 18545 West Creek Dr. • Tinley Park, IL 60477 USA
708-770-7240 • Brian@CruxOrd.com • www.CruxOrd.com



Support Rest
Heavy Duty
CO-001 Instruction Manual

Instructions



Setup:

1. To mount the Support Rest onto a tripod begin by rotating the Base Plate (G) clockwise on the 3/8 inch mounting screw of the tripod. Next, lock the pan knob (F) then using the leverage from the Support Rest, tighten a bit more until snug. If tripod is equipped with Base Set Screw, adjust that to prevent loosening.

2. Open the Picatinny Type Clamp (C) by loosening the Clamp Knob (D) and mount rifle onto the clamp. Lock Clamp Knob (D) securely.

Balancing The Rifle:

3. While holding the Rifle loosen Tilt Lock Knob (A) so the arm is free to swing and also slightly loosening Clamp Knob (D). Now you will be able to slide your rifle forward or backward in the clamp until the Rifle achieves best balance. Once balanced lock the Clamp Knob (D) securely to keep rifle in place.

4. You may also set your resistance on Knobs (A and F) to find a perfect balance between friction and ease of movement for best performance.

Features

- Smooth pan and tilt locking mechanism (separate from assembly mounts)
- Picatinny Type Rifle Mount
- CNC Precision Machined from T6061 aluminum
- Sealed Ball Bearings
- Hard anodized scratch resistant finish
- Made in USA
- 1-year warranty

Maintenance

Check before every use for any loose screws/parts and tighten with knob or supplied hardware. The bearings are sealed and require no lubrication. A small amount of oil (WD40 or similar) may be used on the knobs if necessary. If exposed to potentially corrosive environments, clean with fresh water immediately after use and dry. Taking these precautions will greatly extend the life of the product.

Warranty

This product is guaranteed to the original purchaser to be free of defects in material and workmanship for one (1) year from the date of purchase.

WARNING: Do not over-tighten Pan and Tilt Knobs (A&F) Max Torque: 2.0 Nm/17.7 in-lb

ITAR WARNING: The content or attachments to this document may contain defense technical data covered by the U.S. Munitions List and International Traffic in Arms Regulations. US State Dept. authority for export of such technical data from US is required. Re-export, re-transfer, or disclosure to unauthorized parties, including non-US Persons is prohibited



#GK Specifications:

Length..... 10.50 inches (267mm)
Width.....3 inches (76mm) 4.30 inches (109mm) with knob
Height13 inches (330mm)
Weight..... 5.58 pounds / 2531g
Max Suggested Rifle Weight..... 40 pounds / 18 kg
Tripod Mount.....3/8"-16